

SPIROTECH SPECIFICATION SHEET




MultiControlKompact 45 maxi-4.0-Twin

Customer:

Project:

Reference:

Type: **EMCK-M45-4.0-TWIN**



Design criteria

Medium:	Water / glycol (max 40%)
Min. Pressure:	1.0 bar-g
Discharge:	4.0 bar-g
Max. pressure:	10.0 bar-g
Max. temperature:	70 °C
Ambient temperature:	0 - 40 °C
Refill fluid:	0 - 70 °C

Testing and quality assurance

Running test:	yes
Test medium:	Water
High voltage test:	yes
Test certificate:	no
CE-marking:	yes
Material certificates:	no

Construction materials

Fittings / pipes:	Copper/Brass
Pump:	AISI316
Main pump:	Horizontal multistage 2 x 100%
Overflow valve(s)	2 x 100%
Casing:	Galvanised steel plate
Color:	Yellow (RAL 1003)

Power supply

Voltage:	[1x] 230V~/50Hz
Power consumption:	1.1 kW
Protection level:	IPX4D

Dimensions

Height:	1396 mm
Width:	850 mm
Depth:	725 mm
B	850 mm
F	422 mm
G	322 mm
H	1396 mm
M	512 mm
MM	364 mm
T	725 mm

Dry weight (approx): 108 kg

Connections

1. Refill	Rp1/2
2. Exp. overflow pipe	Rp1
3. Exp. pressure pipe	Rp1
4. Discharge	DN50 Geberit

Subject to changes