



# Product data sheet Spirotech

## ETIM product data

|                                 |                         |
|---------------------------------|-------------------------|
| Housing material                | Brass                   |
| With drain tap                  | Yes                     |
| Housing material quality        | Other                   |
| Backwash filter                 | No                      |
| Medium temperature (continuous) | 0 - 110 °C              |
| Max. operating pressure         | 10 bar                  |
| Kvs value                       | 10.96 m <sup>3</sup> /h |
| Variable flow direction         | Yes                     |
| With insulation                 | No                      |
| Separator type                  | Dirt                    |
| Connection                      | Compression ring        |
| Model                           | Horizontal              |
| Nominal diameter                | Other                   |
| Max. glycol mixture             | 50 %                    |
| Suitable for heating            | Yes                     |
| Suitable for cooling            | Yes                     |
| Outer pipe diameter             | 22 mm                   |
| Construction length             | 106 mm                  |
| Article compression class       | PN 10                   |

|                                       |                           |
|---------------------------------------|---------------------------|
| Surface protection                    | Untreated                 |
| Suitable for open system              | No                        |
| Suitable for closed system            | Yes                       |
| Suitable for solar                    | No                        |
| Whirl operating principle             | No                        |
| Negative pressure operating principle | No                        |
| With dismountable filter              | No                        |
| Filter volume                         | 0.18 l                    |
| Magnet operating principle            | No                        |
| Thrust operating principle            | No                        |
| With automatic de-aerator             | No                        |
| Partial flow principle                | No                        |
| Principle full flow with settling     | Yes                       |
| Cleaning possible during operation    | Yes                       |
| With couplers                         | Yes                       |
| Inlet/outlet offset distance          | 0 mm                      |
| Material of connection                | Brass                     |
| Material quality connection           | Other                     |
| Flow-through capacity                 | 0 - 1.3 m <sup>3</sup> /h |

### Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.

