## **Product data sheet Spirotech**

**Product name** 

SpiroTrap -DN200 -Magnet -Flange

#### **Product properties**

A steel dirt separator with magnet for standard flow rate (1.5 m/s) with a DN50 - DN300 PN16 flange connection

- Very small particles, from 5  $\mu m$  (= 0.005 mm) are separated and removed
- Integrated magnet for extra protection and removal of magnetite
- Dirt can be drained while the system is in operation
- No shut-off valves or bypass required
- Applicable with 50/50 Ethylene Glycol / Water (Volume)
- Constant low pressure drop
- Maintenance only takes a few seconds
- No unnecessary downtime
- PN16 flange connection
- Connection diameters from DN50 to DN 300, larger connection diameters on request


Article number

### **BE200FM**

**Product image** 



#### **Product dimensions**





# **Product data sheet Spirotech**

## ETIM product data

Steel
Yes
St 37 (1.0254)
No
0 - 110 °C
10 bar
743.9
Yes
No
Dirt
Flange
Horizontal
DN 200
50 %
Yes
Yes
775 mm
PN 10
Lacquered
No

Suitable for closed system	Yes
Suitable for solar	No
Whirl operating principle	No
Negative pressure operating principle	No
With dismountable filter	No
Filter volume	105 I
Magnet operating principle	Yes
Thrust operating principle	No
With automatic de-aerator	No
Partial flow principle	No
Principle full flow with settling	Yes
With integrated replenishment automat	No
With couplers	Yes
Cleaning possible during operation	Yes
Material of connection	Steel
Inlet/outlet offset distance	0 mm
Flow-through capacity	0 - 180 m <sup>3</sup> /h
Operating principle	Magnet
Magnet location	Internal
Flange standard	DIN

#### Disclaimer

This product sheet has been compiled with the greatest possible care. Nevertheless, it may contain errors or omissions. For the most current and correct information we refer you to our website.



